



17 KEY BUMP BAR

Designed for Kitchen Video System Applications

CUSTOMIZATION

- Color
- Legends
- Interfaces
- Company Logos
- More Options Available Upon Request

INTERFACE

- Wired: USB, PS2, RS232
- Wireless: Custom Wireless Protocol Between Transmitter and Receiver

FEATURES

- 17 Key Sealed Membrane Input Surface
- Interfaces With Current Kitchen Video System
- Tuff-Key Technology
- High Quality and Durable
- Easy Installation
- Relegendable Quick and Easy to Change
- Mechanical Key Switches for Dependable, Durable Operation
- Splash / Spill Proof Design - Provides Protection to its Components
- Standard and Custom Mounting Solutions Available
- Top or Side Mounting Antenna Configuration
- 50 Million Actuations Per Key

SPECIFICATIONS

- Storage Temperature: -40C to +70C
- Operating Temperature: 0C to +70C
- Dimensions: 9.96 x 2.96 x 1.05 in (253 x 75 x 27 mm)
- Weight: Max 1.55 lbs (0.703 kg)

TG3 PART NUMBER	DESCRIPTION
KBA-BB17-WR-TS-RC	Wireless, Duraswitch, Receiver RS232
KBA-BB17-WR-TU-RC	Wireless, Duraswitch, Receiver USB
KBA-BB17-WR-TP-RC	Wireless, Duraswitch, Receiver PS2
KBA-BB17-WT-T-RC	Wireless, Duraswitch, Transmitter
KBA-BB17-TE-TS-RC	Tethered, Duraswitch, RS232
KBA-BB17-TE-TU-RC	Tethered, Duraswitch, USB
KBA-BB17-TE-TP-RC	Tethered, Duraswitch, PS2