



RUGGED KEYBOARD

Designed for Public Safety
and Mobile Data
Applications

SPECIFICATIONS

- Storage Temperature: -20C to +70C
- Operating Temperature: -20C to +70C
- Operating Humidity: 100%
- Dimensions: 12.00 x 7.75 x 1.25 in (340.85 x 196.85 x 31.75 mm)?
- Weight: 2 lbs?

COMPLIANT

- CE
- FCC
- RoHS

FEATURES

- 83 Keys
- RGB (Red, Green, Blue) Backlighting Rated For Life of the Product (200,000 hr LED's)
- Ergonomic Design and Feel
- Tactile Full Travel Key Switches
- Embedded Multi-Media Functionality
- Chemical Resistant Engineered Plastic Resin
- Splash-Proof Touchpad With 2 Sealed Mouse Buttons
- 10 Million Actuations Per Key
- New tooling for top housing with ribs to protect the keys
- Lithium Ion Battery Pack
- TG3 Logo on Bottom Cover
- 8 Threaded inserts: 4 Vesa 75 mount & 4 PEM Mount
- Two Cables Included

ELECTRICAL SPECIFICATIONS

- Voltage: +5Vdc From Data Cord
- Radiated Immunity: 20 Volts / Meter
- Backlight Dimming Includes 8 Levels of Intensity Controlled by "Fn" + "0" - "7"
- X/Y Position Resolution: 500 Points / Inch (20 Points Max)

INTERFACE

- Dual Compatibility
 - a. Detachable USB-C Cables (Straight and coiled cable)
 - b. Bluetooth BLE

TG3 PART NUMBER	DESCRIPTION
KBA-BLTX-BT-US	Black, BLE, USB, Backlit