



RUGGED LOW PROFILE KEYBOARD

Designed for Public Safety
and Mobile Data
Applications

SPECIFICATIONS

- Storage Temperature: -55C to +85C
- Operating Temperature: -40C to +70C
- Operating Humidity: 100%
- Dimensions: 10.7 x 7.0 x .6 in (271 x 177 x 16 mm)
- Weight: 1.5 lbs

COMPLIANT

- FCC
- CE
- RoHS

INTERFACE

- USB
- Bluetooth

FEATURES

- 79 Keys
- RGB Backlighting Rated For Life of the Product (20,000 hr. LED's)
- Low Cost, Ultra Rugged Keyboard
- Low Profile With Ergonomic Design and Feel
- Slim Small Footprint space-saver
- Tactile Low Travel Key Switches allow for faster actuation
- Embedded Multi-Media Functionality
- Chemical Resistant Engineered Plastic Resin Housing and Keycaps
- Splash-Proof Touchpad With 2 Sealed Mouse Buttons
- 10 Million Actuations Per Key
- VESA 75 and AMPS Mounting Options are Standard
- Ideal for Mobile Mounting Solutions
- Backlight Dimming ideal for nighttime or ambient-light use
- Proven Quality and a 3-Year Warranty

ELECTRICAL SPECIFICATIONS

- Voltage: +5Vdc @ 500mA Max From Data Cord
- Compatible with Root USB Ports (on PC) or Self-Powered Hubs
- Radiated Immunity: 20 Volts / Meter
- X/Y Position Resolution: 500 Points / Inch (20 Points Max)

FUNCTIONS

- FN+F2 (Windows Settings)
- FN+F3 (Screen Brightness Down)
- FN+F4 (Screen Brightness Up)
- FN+F5 (Volume Down)
- FN+F6 (Volume Up)
- FN+F7 (Mute)
- FN+F9 (Screen Off)
- FN+F10 (Keyboard Brightness Down)
- FN+F11 (Keyboard Brightness Up)

Additional functions available on website.

TG3 PART NUMBER

DESCRIPTION

KBA-BLTXR-LPU-US

Black, USB, Straight & Coiled
Cord, Backlit